

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 1	Of: 13

Nuraghe schedule structure

	Name	Date	Signature
Authors	Righini S (IRA) Orlati A (IRA) Bartolini M (IRA)	26/01/15	



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 2	Of: 13

	DOCUMENT CHANGE RECORD						
lssue No.	lssue date	No. of pages	Pages changed, added, deleted	Description of change			
01	02/02/15	13		Issue 01			

1 SC	HEDL	ULE STRUCTURE	
1.1	Sca	AN-SUBSCAN OBSERVATIONS	
1.2	Sch	HEDULE FILES	4
1	2.1	SCD file	4
1	2.2	LIS file	7
1	2.3	CFG file	
1	2.4	BCK file	
1	2.5	DAT file	



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 3	Of: 13

1 Schedule structure

A schedule is a set of files where all the geometry/timing/frequency details of a sequence of data acquisitions are specified, according to a syntax that enables Nuraghe to read and execute them. In order to generate the schedules, for the most common observing modes in continuum and (partially) spectroscopy, a tool called *ScheduleCreator* is available (see IRA Technical Report 266/13).

For regular observations, **users should not edit the schedule files**: for most of the applications, they can totally ignore what is written inside them. Only expert users, wanting to customize their observations in unusual or complex ways, should access the schedules and edit them, or create schedules from scratch using their own tools.

For this purpose, the following sections describe the general scheme conceived for the observations and the content of the files composing the schedule.

1.1 Scan-subscan observations

We define the *scans* and *subscans* composing the observing session as follows:

Scan

It is the lowest level object normally used by an observer. *It is a sequence of one or more subscans that share a single goal*: for instance cross-scans and maps involve a pattern of subscans. Whether OTF maps mosaicing observations are considered a single scan or a series of scans is rather a matter of how the user would like to define it. In our implementation each map is considered a scan.

Subscan

it is the minimal amount of data acquisition that can be commanded at the script language level. It is highly desirable that it is a simple enough element. For example, it is the single OTF "line" of a map or of a cross-scan.

The figure below visually represents what cross-scans, OTF maps and raster maps are.



In the case of cross-scan, a subscan is a single arrow (a line across the target), four arrows – i.e. two full crosses – constitute the schema which might be repeated as many times as needed within the scan. For OTF maps, the subscan is again the single arrow, and the scan coincides with the whole map obtained with lines along one axis only (e.g. along RA or Dec). For raster maps, which are based on discrete acquisitions, each point is a subscan, and the final map constitutes the scan.

When choosing FITS as the data output format, a distinct FITS file is produced for each subscan listed in the schedule.



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 4	Of: 13

The scan-subscan dependency is more evident when MBFITS are created, as the observation arrangements illustrated above reflect into a hierarchical structure for the several folders and files that constitute the MBFITS.

Details on the file production are given in the next section, where the .scd component of the schedule is described.

1.2 Schedule files

The present release of the system requires a 4+1 files:

- .scd file: it holds the sequence of scans/subscans to be performed
- .lis file: it lists the spatial configuration of the single subscans composing the observation
- .cfg file: it contains the frontend configuration and other procedures to be used in the initialization phase (if any) and in the pre-scan/post-scan operations (if any). Any Nuraghe command can be inserted in these procedures. Users are warned, however, that their employment might not be necessarily useful: pay attention to the meaningfulness of their insertion within the schedules.
- .bck file: it is devoted to the backend setup
- .dat file: this file is used only in case the MBFITS output format is chosen, as it contains information that is not read by Nuraghe but is needed in the writing phase of the file.

1.2.1 SCD file

This is the main schedule file, listing the scans/subscans to be executed.

In case of a sequential schedule, scans/subscans are not associated to specific execution times, so they are carried out sequentially following an "as soon as possible" approach.

Values are all TAB-separated.

The header must contain the following keywords, including the final colon:

PROJECT: OBSERVER:	user-defined label for the project. It will end up in the output filename. name of the observer. It will end up in one FITS file header.
SCANLIST:	name of the LIS file to be used.
PROCEDURELIST:	name of the CFG file to be used.
BACKENDLIST:	name of the BCK file to be used.
MODE:	schedule mode: SEQ for sequential schedules, LST for time-based schedules. If SEQ, then a tab-separated start LST time can be specified as HH:MM:SS. If LST, then a tab-separated value can indicate how many
times	
[INITPROC: [SCANLAYOUT:	the schedule must be run name of the initialization procedure (contained in the CFG file), optional] name of the DAT file (for MBFITS only, otherwise it has no effect)]

Then, the scans/subscans are listed.

Each scan is introduced by a line starting with "SC:" followed by some scan-level information:



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 5	Of: 13

SC: Scan# ScanLabel BCKProcedure:WriterName [ScanLayoutName]

Scan#is the number for the scan. It must be unique in the schedule. Scan numbers must
be incremental but do not need to be sequential.ScanLabelwill be included in the output filename.

BCKProcedure is the name of a valid procedure listed in the BCK file.

WriterName is the name of the output data writer (MANAGEMENT/FitsZilla or

MANAGEMENT/MBFitsWriter).

ScanLayoutName is the name of the layout selected from the DAT file. It should be omitted, as it is useless, when FITS files are chosen for data output.

After the scan setup, all the subscans composing that scan are specified, like:

Scan#_	_subscan#	Duration	SubscanID	PreProcedure PostProcedure
	Scan#_subscar	n# is the s	sequential numb	er for the subscan, e.g. 1_1, 1_2, etc
	Duration	is the s the du	subscan duration ration declared in	(seconds). For OTF subscans it must coincide with the LIS file
	SubscanID	is the I	D for the subsca	in to be executed, as reported in the LIS file
	PreProcedure	is the r the PC	name of the proc OST-subscan pha	edure, enclosed in the CFG file, to be performed in ase. Parameters can be passed as name=value.
	PostProcedure	is the he pos	name of the pro	cedure, present in the CFG file, to be performed in e. Parameters can be passed as name=value.

Here follows an example of sequential schedule where the chosen output file format is FITS.

OBSERVER: John Doe SCANLIST: Test3c295.lis PROCEDURELIST: Test3c295.cfg BACKENDLIST: Test3c295.bck MODE: SEQ INITPROC: INIT SC: 1 300_40 1_1 0.0 1 NULL SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POST 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	PROJE	CT:	Test3c2	295	
SCANLIST: Test3c295.lis PROCEDURELIST: Test3c295.cfg BACKENDLIST: Test3c295.bck MODE: SEQ INITPROC: INIT SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTT 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	OBSEF	RVER:	John D	oe	
PROCEDURELIST: Test3c295.cfg BACKENDLIST: Test3c295.bck MODE: SEQ INITPROC: INIT SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL J_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTT 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	SCANL	IST:	Test3c2	295.lis	
BACKENDLIST: Test3c295.bck MODE: SEQ INIT SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POST 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 7 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	PROCE	EDUREL	IST:	Test3c2	295.cfg
MODE: SEQ INIT SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	BACKE	NDLIST	-:	Test3c2	295.bck
INITPROC: INIT SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	MODE:	SEQ			
SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	INITPR	OC:	INIT		
SC: 1 300_40 300_40:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0					
1_1 0.0 1 NULL POSTTSYS 1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL POST 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	SC:	1	300_40	300_40	:MANAGEMENT/FitsZilla
1_2 14.0 5 NULL POST 1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	1_1	0.0	1	NULL	POSTTSYS
1_3 14.0 6 NULL POST 1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	1_2	14.0	5	NULL	POST
1_4 14.0 7 NULL POST 1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	1_3	14.0	6	NULL	POST
1_5 14.0 8 NULL WAIT=1.0 SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	1_4	14.0	7	NULL	POST
SC: 2 730_20 730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	1_5	14.0	8	NULL	WAIT=1.0
SC: 2 730_20730_20:MANAGEMENT/FitsZilla 2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0					
2_1 0.0 1 NULL POSTTSYS 2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	SC:	2	730_20	730_20	:MANAGEMENT/FitsZilla
2_2 14.0 5 NULL POST 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	2_1	0.0	1	NULL	POSTTSYS
2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	2_2	14.0	5	NULL	POST
2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0	2_3	14.0	6	NULL	POST
2_5 14.0 8 NULL WAIT=1.0	2_4	14.0	7	NULL	POST
	2_5	14.0	8	NULL	WAIT=1.0

Please notice that sequential schedules **run ad libitum**, as long as the targets are above the horizon and the user does not input a *stopSchedule* command.



1_4

14.0

7

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 6	Of: 13

An equivalent schedule, this time for **MBFITS** output files, could be:

PROJECT: Test3c295 OBSERVER: John Doe SCANLIST: Test3c295.lis PROCEDURELIST: Test3c295.cfg BACKENDLIST: Test3c295.bck MODE: SEQ **INITPROC:** INIT SCANLAYOUT:Test3c295.dat SC: 1 300_40 300_40:MANAGEMENT/MBFitsWriter scanLayout_0001_3C295 1_1 0.0 NULL POSTTSYS 1 1_2 NULL POST 14.0 5 NULL POST 1_3 14.0 6

NULL POST

15 NULL WAIT=1.0 14.0 8 SC: 2 730 20 730 20:MANAGEMENT/MBFitsWriter scanLayout 0002 3C295 2 1 0.0 NULL POSTTSYS 1 22 14.0 NULL POST 5 2_3 14.0 6 NULL POST 2_4 14.0 7 NULL POST 2_5 14.0 8 NULL WAIT=1.0

It is possible to write **sidereal-time-based schedules**, assigning the 'LST' value to the header keyword 'MODE', followed by the number of repetitions foreseen for the schedule (1 means that, when the schedule has completed one run, it stops). It is then necessary to add a column to the SCD file, where the LST start times for the individual subscans are provided. This feature is not included in the present release of the *schedulecreator*, so **this schedule version can be obtained only editing a sequential schedule**, or using custom tools.

The single subscan line then becomes:

Scan#	subscan#	StartLST	Duration	SubscanID	PreProcedure	PostProcedure

Here is an example of time-based schedule:

PROJECT: Test3c295 OBSERVER: John Doe SCANLIST: Test3c295.lis PROCEDURELIST: Test3c295.cfg BACKENDLIST: Test3c295.bck MODE: LST 1 INITPROC: INIT

1 300_4	40 300_4	0:MA	NAGEMEN	T/FitsZilla
12:23:35.0	0.0	1	NULL	POSTTSYS
12:23:40.0	14.0	5	NULL	POST
12:24:00.0	14.0	6	NULL	POST
12:24:20.0	14.0	7	NULL	POST
12:24:40.0	14.0	8	NULL	POST
	1 300_4 12:23:35.0 12:23:40.0 12:24:00.0 12:24:20.0 12:24:40.0	1300_40 300_412:23:35.00.012:23:40.014.012:24:00.014.012:24:20.014.012:24:40.014.0	1300_40 300_40:MA12:23:35.00.0112:23:40.014.0512:24:00.014.0612:24:20.014.0712:24:40.014.08	1300_40 300_40:MANAGEMEN12:23:35.00.0112:23:40.014.0512:24:00.014.0612:24:20.014.0712:24:40.014.08



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 7	Of: 13

SC:	2 730_2	20 7 30 2	0:MA	NAGEMEN	T/FitsZilla
2_1	12:26:55.0	0.0	1	NULL	POSTTSYS
2_2	12:27:00.0	14.0	5	NULL	POST
2_3	12:27:20.0	14.0	6	NULL	POST
2_4	12:27:40.0	14.0	7	NULL	POST
2_5	12:28:00.0	14.0	8	NULL	POST

1.2.2 LIS file

This file lists all the spatial subscan configurations employed within the schedule, one for each line. They do not need to follow the execution sequence in which they are called by the SCD schedule: the first column gives a unique incremental ID (not necessarily sequential: gaps are allowed) to be included in the calls inside the SCD file. Fields are **TAB-separated**.

3C295

1	SIDEREAL	TSys	EQ	212.8360d	52.2025d	2000.0	-EQOFFS	0.0d	-0.35d					
2	SIDEREAL	TSys	EQ	212.8360d	52.2025d	2000.0	-EQOFFS	0.0d	0.35d					
3	SIDEREAL	TSys	EQ	212.8360d	52.2025d	2000.0	-EQOFFS	-0.35d	0.0d					
4	SIDEREAL	TSys	EQ	212.8360d	52.2025d	2000.0	-EQOFFS	0.35d	0.0d					
5	OTF3C295	212.8360d	52.2025d	0.0d	0.7d	EQ	EQ	LON	CEN	INC	14.0	-EQOFFS	0.0d	0.0d
6	OTF3C295	212.8360d	52.2025d	0.0d	0.7d	EQ	EQ	LON	CEN	DEC	14.0	-EQOFFS	0.0d	0.0d
7	OTF3C295	212.8360d	52.2025d	0.7d	0.0d	EQ	EQ	LAT	CEN	INC	14.0	-EQOFFS	0.0d	0.0d
8	OTF3C295	212.8360d	52.2025d	0.7d	0.0d	EQ	EQ	LAT	CEN	DEC	14.0	-EQOFFS	0.0d	0.0d

Three different subscan types can be used: <u>SIDEREAL</u>, <u>OTF</u>, <u>OTFC</u> and <u>SKYDIP</u>.

SIDEREAL subscans

They are used for tracking and on-off acquisitions: the antenna points to the specified position. The LIS line is composed by:

LIS line is composed by:
ID = unique ID for the subscan configuration
TYPE = subscan type label, in this case 'SIDEREAL'
TARGET = label for subscan target/content
FRAME = frame for the coordinates to follow. Options: 'EQ', 'HOR' or 'GAL'
LONGITUDE = target longitude, following the generally allowed longitude formats
LATITUDE = target latitude, following the generally allowed latitude formats
EPOCH = for EQ coordinates only. '-1' means the coordinates are precessed to date.
OFFSET LABEL = [opt] frame for the offsets to follow. Options: '-EQOFFS', '-HOROFFS' or '-GALOFFS'
LON OFFSET = [opt] longitude offset (degrees, with 'd' suffix)
LAT OFFSET = [opt] latitude offset (degrees, with 'd' suffix)

→ Notice: the offsets frame can be freely chosen, regardless of the frame describing the target coordinates. These offsets sum up to the overall offsets that might have been defined by the users with the *radecOffsets*, *azelOffsets* and *lonlatOffsets* commands. By default, subscan-level offsets are zeroed any time a new subscan is commanded, and new offsets (if any is specified in the LIS line) take over.

Though the definition SIDEREAL clearly implies the tracking of a celestial source, a "degenerate" use of this subscan type is given by *beam-parking* observations: when users want to acquire data in a fixed Az,El position, they can use SIDEREAL subscans where the coordinate frame is 'HOR'. Please notice that, though this observing mode implies no antenna motion, it fully corresponds to the execution of a schedule with scans/subscans as concerns data acquisition, so the mount must be in tracking mode (and not in preset mode) in order to perform this kind of observation.

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 8	Of: 13

OTF subscans

On-the-fly subscans are paths on the sky run at constant speed while acquiring data.

The LIS line is composed by:

ID = subscan unique ID

TYPE = subscan type, in this case 'OTF'

TARGET = label for target

LON1 = for DESCR='SS' (later keyword), longitude (*) of the scan starting point. For DESCR='CEN',

longitude (*) of the subscan central point.

LAT1 = for DESCR='SS' (later keyword), latitude (!) of the scan starting point. for DESCR='CEN', latitude (!) of the subscan central point.

LON2 = for DESCR='SS' (later keyword), longitude (*) of the subscan ending point. for DESCR='CEN', whole longitude span (*) of the subscan.

LAT2 = for DESCR='SS' (later keyword), latitude (!) of the subscan ending point. for DESCR='CEN',

whole latitude span (!) of the subscan.

FRAME = coordinate frame relative to the previously specified lon-lat coordinates:

'EQ' = Equatorial J2000.0 (longitude = RA, latitude = Dec)

'HOR' = Horizontal (longitude = azimuth, latitude = elevation)

- 'GAL' = Galactic (longitude = I, latitude = b)
- *sFRAME* = coordinate frame along which the scan is performed. It must be equal to FRAME, apart from a single case: if FRAME is 'EQ' and the scan description is 'CEN' (see next keywords), then sFRAME can also be 'HOR', which means that Az-El scans will be performed across a sidereal position. This is usually exploited for pointing calibration campaigns.

GEOM = scan geometry:

- LON = constant longitude
- LAT = constant latitude
- GC = great circle arc (only for DESCR='SS')
- DESCR = scan description:

SS = start and stop positions

CEN = center position + scan span

DIR = scan direction (ignored if GEOM='CG'):

INC = the varying coordinate increases

DEC = the varying coordinate decreases

DURATION = scan actual duration in seconds (acceleration/deceleration ramps excluded)

- offFRAME = [opt] frame for the user-defined offsets to be added to the lon-lat coordinates specified (the leading dash ' –' is compulsory):
 - -EQOFFS = Equatorial
 - -HOROFFS = Horizontal

-GALOFFS = Galactic

At present offFRAME must be equal to sFRAME, which means that it is not possible to perform scans in an exotic way like scanning along the galactic longitude while applying equatorial offsets, etc... but it is possible to apply Az,El offsets to Az,El scans across a sidereal (equatorial) position.

- LONOFF = [opt] longitude offset, in degrees, which can be specified as dd.dd'd' (decimal format, can be positive or negative, notice the 'd' suffix) or dd:mm:ss.s. It is meant to be "on sky", i.e. the actual span, in practice $\Delta lon x \cos(lat)$.
- LATOFF = [opt] longitude offset, in decimal degrees (notice the 'd' suffix).

→ Notice: these offsets sum up to the overall offsets that might have been defined by the users with the *radecOffsets*, *azelOffsets* and *lonlatOffsets* commands. By default, subscanlevel offsets are zeroed any time a new subscan is commanded, and new offsets (if any is specified in the LIS line) take over.



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 9	Of: 13

Examples of valid OTF subscans:

1	OTF	Source1	310.256d	30.231d	310.256d	30.931d	EQ	EQ	LON	SS	INC	14.0			
2	OTF	Source1	310.256d	30.231d	0.0d	0.7d	EQ	EQ	LON	CEN	INC	14.0			
3	OTF	Source2	12:45:12h	18:12:21.1	0.7d	0.0d	EQ	HOR	LAT	CEN	INC	14.0	-HOROFFS	-1.0d	0.0d
4	OTF	Source3	21.738d	88.205d	0.7d	0.0d	GAL	GAL	LAT	CEN	DEC	14.0	-GALOFFS	0.0d	1.0d

Subscans #1 and #2 are totally equivalent, as they only differ in the decription: the first gives the start-stop boundaries of the subscan, while the second expresses the same in terms of center+span.

Subscan #3 is a horizontal subscan (in particular it is 'LAT'=constant elevation), executed across a sidereal position, in this case expressed with sexagesimal coordinates, with -1 degree of azimuth offset.

Subscan #4 is performed in the Galactic frame, but with an offset of +1 degree in latitude. Notice that the subscan direction is 'DEC', so the subscan will be performed 'backwards', i.e. with longitude decreasing along the execution.

OTFC subscans

These OTF acquisitions are performed using an externally-defined target position. The target is recovered from a separate subscan, whose ID is specified among the OTFC parameters:

ID = subscan unique ID TYPE = subscan type, in this case 'OTFC' TARGET_ID = ID of the subscan where the target position is defined SPAN = span of the subscan (degrees) FRAME = target coordinate frame ('EQ' or 'GAL') sFRAME = coordinate frame along which the scan is performed ('EQ', 'HOR' or 'GAL') GEOM = scan geometry: LON = constant longitude LAT = constant latitude DIR = scan direction:

INC = the varying coordinate increases

DEC = the varying coordinate decreases

DURATION = scan actual duration in seconds (acceleration/deceleration ramps excluded)

Example of usage of OTFC subscans:

1	SIDERE	۹L	3c147						
2	SIDERE	۹L	MySour	ce	EQ	12:00:0)0h	30:00:00	2000.0
3	OTFC	1	1.0d	EQ	EQ	LAT	INC	14.0	
4	OTFC	1	1.0d	EQ	EQ	LON	INC	14.0	
5	OTFC	2	2.0d	GAL	GAL	LAT	INC	28.0	
6	OTFC	2	2.0d	GAL	GAL	LON	INC	28.0	

Subscans #1 and #2 are simple SIDEREAL subscans; notice that, as the first one invokes a target which is listed in the system catalogue (Appendix E), the target coordinates are not specified.

Numbers #3 and #4 are OTFC subscans centered on the position inserted in subscan #1; they grab the EQ coordinates of 3c147 from the catalogue and respectively perform a Dec and a RA subscan across the source, each spanning 1 degree in 14 seconds.

Subscans #5 and #6, instead, refer to the second SIDEREAL, the one devoted to 'MySource'. The target coordinates in subscan #2 are given in the Equatorial frame, however the OTFC calls them in the Galactic frame: in this case the target Equatorial coordinates are converted to Galactic coordinates and then passed to the OTF component of the system.

 \rightarrow <u>Notice</u>: when a SIDEREAL subscan is used as a reference for an OTFC subscan, the offsets specified in the SIDEREAL one, if any, are ignored.

The present usage of OTFC subscans looks convoluted: it is mainly conceived for observations of moving targets (with the employment of an ephemeris generator component, under development).



Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 10	Of: 13

SKYDIP subscans

A skydip can be achieved by properly setting a normal OTF subscan in the HOR frame, but this requires the user to already fix the azimuth position at which the skydip must be performed.

A more dynamical solution, described in the following paragraph, allows the observer to schedule a skydip in the nearbies of a given source.

To achieve this, here is an example of the lines which must be inserted in the .LIS file:

1 SIDEREAL MySource EQ 12:00:00h 30:00:00 2000.0 -HOROFFS -1.0d 0.0d 2 SKYDIP 1 20.0d 90.0d 300.0 -HOROFFS -1.0d 0.0d

The first line is a normal SIDEREAL subscan, pointing to an offset position w.r.t. a certain source of given celestial coordinates.

The second line is composed by:

ID = subscan unique ID *TYPE* = subscan type, in this case 'SKYDIP' *REFERENCE_SIDEREAL* = subscan ID identifying the reference SIDEREAL position *START_EL* = elevation of skydip starting point (degrees, 0-90), with "d" suffix *STOP_EL* = elevation of skydip ending point (degrees, 0-90), with "d" suffix *DURATION* = subscan duration (seconds) *offFRAME* = use -HOROFFS only *LONOFF* = longitude offset (degrees), with "d" suffix *LATOFF* = latitude offset (degrees), with "d" suffix (usually 0.0d)

The corresponding subscan definition in .SCD file would be:

SC: 1 MySource Skydip STD:MANAGEMENT/FitsZilla 1_1 0.0 1 NULL PROCEDURE_TSYS 1_2 300.0 2 NULL POST

Where PROCEDURE_TSYS and POST are proper procedures written in the .CFG file (see next paragraph).

The result of the combination of the two actions is: the telescope goes off of 1.0° in azimuth with respect the target MySource, a tsys is measured. Then the current azimuth of the source (minus 1 degree) is used as the reference azimuth to perform the skydip, spanning beween 20° and 90° of elevation in 300 seconds.

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 11	Of: 13

1.2.3 CFG file

This file lists the (optional) configuration parameters for the frontend frequency and for the execution of some procedures that the users might want to run before or after a scan.

The first field is the name of the procedure which is user-defined and must be unique in the file. Names are case sensitive. It is suggested to use all-caps names, so that any name clash with Nuraghe commands is impossible.

The open bracket must lie on the same line of the procedure name. Between brackets the configuration commands must be provided one for each line. The .cfg file can contain as many procedures as needed.

An example of a possible content of the .cfg file:

```
INIT{
   setLO=5600
   device=0
}
LOW_FREQ{
   setl O=5650
   device=0
}
HI FREQ{
   setLO=5700
   device=0
}
PRESCAN{
   nop
}
POSTTSYS{
   wait=3.000
   tsys
}
DELAY{
   wait=3.000
}
WAIT(1){
   wait=$0
}
```

Observers might create a procedure like *INIT* (again, the name is user-defined), conceived to be called only once, when the schedule is loaded. One useful command to be inserted inside this call is the "setLO" one, to specify the local oscillator frequency value (MHz): this frequency setup can be manually performed during the overall system setup phase, but it also can be changed for each schedule inserting this command in the initialization procedure, or even at subscan level as shown in procedures *LOW_FREQ* and *HI_FREQ* to be used in the pre-scan phase. For spectroscopy, do NOT use the "setLO" command, as the local oscillator frequency is computed by the system in order to properly observe the wanted line, whose actual sky frequency depends on date and time.

The next four procedures shown above are meant to be called before and after the execution of the actual subscan, and can be named as the user prefers: remember that their name must be correspondingly called inside the .scd file (see next section).

In the above example, if the procedure *POSTTSYS* is called after a certain subscan, a T_{sys} will be measured 3 seconds after the antenna has closed the subscan acquisition and before the next subscan is commanded. Please notice that these commands are NOT time-based: they will be executed sequentially.

SRT

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 12	Of: 13

The above example of a post-scan procedure (*DELAY*), if called for a given subscan, means that - after its completion - the system will wait for 3 seconds before commanding the next one to the antenna. This is done to let the antenna complete the deceleration ramp before slewing to another subscan, as abrupt stops and turnabouts in the antenna motion can cause unpleasant (and potentially hazardous) oscillations of the mount.

Users can define procedures accepting one or more arguments, to be passed when the procedures are called. One example is the *WAIT* procedure: after its name, the number in () brackets specifies how many arguments it has. Inside this procedure, there is only a *wait* command, where the "\$0" is a reference for the value that will be passed at runtime. \rightarrow *Beware: this feature is not yet fully debugged*.

Ideally, any Nuraghe command can be inserted into these procedures. This does NOT mean it should be done, as many of them have no useful role within a schedule – on the contrary, their effects might be detrimental on the results. Users are warned that the execution of "creative" schedules might lead to unexpected or unwanted results.

Commands can be temporized, i.e. a specific UT time can be associated to them, in order to command their execution in a given moment. This is accomplished appending a time indication in the form "@DOY-HH:MM:SS", for example:

tsys@124-13:44:23

Again, this opportunity must be exploited *cum grano salis*.

1.2.4 BCK file

The content of this file is devoted to the backend configuration. As in the .CFG file, it lists the procedures to be called within the .SCD schedule.

As the following example shows, each procedure must have a unique name and make reference to the selected backend (in this case: BACKENDS/TotalPower). The open bracket must line in the same line of the procedure name, then the backend-related commands must be inserted – one per line.

```
STD:BACKENDS/TotalPower {
    setSection=0,*,2000.0,*,*,0.000025,*
    setSection=1,*,2000.0,*,*,0.000025,*
    integration=40
    enable=1;1
}
300_40:BACKENDS/TotalPower {
    setSection=0,*,300.0,*,*,0.000025,*
    setSection=1,*,300.0,*,*,0.000025,*
    integration=40
    enable=1;1
}
730_20:BACKENDS/TotalPower {
    setSection=0,*,730.0,*,*,0.00005,*
    setSection=1,*,730.0,*,*,0.00005,*
    integration=20
    enable=1;1
}
```

Notice the 'enable' command, which positionally specifies the sections that are meant to be acquiring data (0 equals to 'off', 1 to 'on'). If, for example, only the feeds 0 and 5 of the MF receiver are required to observe, the command for the TPB would be: enable=1,1,0,0,0,0,0,0,1,1,0,0

It is important to give the *integration* command <u>after</u> the setSection one, when the integration value differs from the sampling time commanded by setSection.

SRT

Doc. No.:	SRT-MAN-10000-004	Issue No.: Issue Date:	01 02/02/15
Title:	Nuraghe schedule structure	Page: 13	Of: 13

1.2.5 DAT file

This auxiliary text file is needed only when the selected output format is MBFITS.

It contains, in fact, information that is not required to run the schedule, or is redundant with respect to the commands sent to the ScheduleExecutor component of Nuraghe, but which is compulsory to fill in the headers/tables in the MBFITS files.

The exact content depends on the selected observing mode (continuum or spectroscopy).

Details will be provided as the MBFITS output option is fully tested and made available.